

COMBINATION LED AND STROBE LIGHTING DEVICE

CROSS-REFERENCE TO RELATED APPLICATION

5 [0001] This application is related to Application No. xx/xxx,xxx entitled, "Automatic Selection of Illumination Source for Hybrid Digital Cameras," filed on or about the same date as the present application, and hereby incorporated herein by reference. Application No. xx/xxx,xxx discloses and claims a method for the automatic selection
10 of illumination sources by digital cameras.

FIELD OF THE INVENTION

[0002] The present invention relates generally to the field of photography and more
15 specifically to the field of lighting of photographic subjects for still and video imaging.

BACKGROUND OF THE INVENTION

[0003] Many modern digital cameras include both a still photography mode and a video
20 mode. In the video mode, short moving video clips are captured by the digital camera. These video clips may range in length from a few seconds to several minutes. The lighting requirements for these two modes of operation are significantly different. In digital still cameras a very bright flash for scene illumination is often desired so that high shutter speeds can be used to stop and freeze any motion in the
25 scene being captured. In video mode, a more uniform constant light source is desired.

SUMMARY OF THE INVENTION

[0004] A lighting device for a digital camera is built including one or more light emitting diodes (LEDs) along with a strobe. The LEDs are configured to provide lighting of the subject during a video mode of the camera and the strobe is configured to provide lighting of the subject during a still mode of the camera. These independent light sources may share a common reflector in some embodiments, while in other embodiments they may use separate reflectors. This lighting device may be built-in to a digital camera or in some embodiments may be configured as a separate device controlled by the digital camera.

[0005] Other aspects and advantages of the present invention will become apparent from the following detailed description, taken in conjunction with the accompanying drawings, illustrating by way of example the principles of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] Figure 1 is front view of an example embodiment of a digital camera including a LED and strobe lighting device according to the present invention.

[0007] Figure 2 is front view of an example embodiment of a digital camera attached to a lighting device including a LED and a strobe according to the present invention.

[0008] Figure 3 is a cross-sectional view of a lighting device including two LEDs, a strobe, and a single reflector according to the present invention.

[0009] Figure 4 is a cross-sectional view of a lighting device including one LED, a strobe, and two reflectors according to the present invention.

DETAILED DESCRIPTION

[0010] Figure 1 is front view of an example embodiment of a digital camera including a LED and strobe lighting device according to the present invention. An example embodiment of a camera **100** constructed according to the present invention may include a camera body **102**, a lens **106**, a LED and strobe lighting device **104**, an external viewfinder window **108**, a shutter release **110**, and a control **112**. As with all digital cameras, this example embodiment of the present invention includes a circuit **114** electrically connected to the shutter release **110**, electrically connected to the LED and strobe lighting device **104**, and configured to control the lighting device **104** by activating either the LED or the strobe within the lighting device. This circuit **114** includes a means for detecting when the shutter release **110** is depressed. In some example embodiments of the present invention, the circuit **114** may also be configured to detect when the shutter release **110** is partially depressed. In an example embodiment of the present invention, the control **112** may be used to select a mode of the digital camera. These modes may include a still photo mode and a video mode.

[0011] Figure 2 is front view of an example embodiment of a digital camera attached to a lighting device including a LED and a strobe according to the present invention. In this embodiment of the present invention the lighting device including a LED and a strobe is configured as a separate device from the digital camera. Similar to the digital camera of Figure 1, this example embodiment of a camera includes a camera body **202**, a lens **206**, an external viewfinder window **208**, a shutter release **210**, a control **212**, a hot shoe **220** including hot shoe electrical contacts **222**. As with all digital cameras, this example embodiment of the present invention includes a circuit **224** electrically connected to the shutter release **210**, electrically connected to the hot shoe electrical contacts **222** and the flash control outputs **218**. The circuit **224** is

configured to control one or more external lighting devices through the hot shoe electrical contacts **222** or the flash control outputs **218**. This circuit **224** includes a means for detecting when the shutter release **210** is depressed. In some example embodiments of the present invention, the circuit **224** may also be configured to
5 detect when the shutter release **210** is partially depressed. In an example embodiment of the present invention, the control **212** may be used to select a mode of the digital camera. These modes may include a still photo mode and a video mode. This example embodiment also includes dedicated flash control outputs **218** separate from the hot shoe electrical contacts **222**. Both the flash control outputs **218** and the hot
10 shoe electrical contacts **222** may be used to control a mode of the lighting device **200**. This example embodiment of a lighting device **200** includes a combined LED and strobe **204**, flash control inputs **216**, and a switch **214**. The flash control inputs **216** and the switch **214** may be used to select a mode of the flash. In a still mode, the strobe of the flash is activated when triggered by the camera. In a video mode, the
15 LED is activated when triggered by the camera. In an example embodiment of the present invention, the switch **214** may allow a user to override the mode signal communicated from the camera through the flash control outputs **218** into the flash control inputs **216** of the lighting device **200**.

[0012] Figure 3 is a cross-sectional view of a lighting device including two LEDs, a
20 strobe, and a single reflector according to the present invention. In this example embodiment of the present invention a lighting device **300** is built including a body **302** with supports **312** for a reflector **308** and a lens **310**. In this example embodiment two LEDs **306** share the common reflector **308** with a strobe tube **304**. Those of skill in the art will recognize that many different configurations of LEDs and strobe tubes
25 may be used within the scope of the present invention. While this example

embodiment includes two LEDs **306** positioned on either side of a strobe tube **304**. Other embodiments may use any number of LEDs **306** positioned in widely varying locations with respect to the strobe tube **304**. Also, other embodiments of the present invention may use more than one strobe tube **304**.

5 **[0013]** Figure 4 is a cross-sectional view of a lighting device including one LED, a strobe, and two reflectors according to the present invention. In this example embodiment of the present invention a lighting device **400** is built including a body with supports **414** configured to mechanically affix a first reflector **406**, a first lens **410**, a second reflector **408**, and a second lens **412**. A strobe tube **402** is configured to
10 use the first reflector **406** and the first lens **410**, while a LED **404** is configured to use the second reflector **408** and the second lens **412**. This embodiment of the present invention includes a hot shoe foot **416** including flash input connections **418** configured to electrically couple to the hot shoe of the camera shown in Figure 2. Those of skill in the art will recognize that many different quantities and
15 configurations of strobe tubes and LEDs may be used within the scope of the present invention. While many implementations of the present invention will use white LEDs for video illumination, other colors of LEDs may be used either in place of, or in addition to white LEDs to change the color of the light generated by the lighting device.

20 **[0014]** In other embodiments of the present invention, the LED and strobe illumination device may be configured as a device separate from the camera. It may attach to the camera via a hot shoe, and additional signals within the hot shoe may control the mode of the illumination device. In some simple embodiments of the present invention the mode of the illumination device may be controlled by the user of the
25 camera with a switch.

[0015] The foregoing description of the present invention has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise form disclosed, and other modifications and variations may be possible in light of the above teachings. The embodiments were chosen and described in order to best explain the principles of the invention and its practical application to thereby enable others skilled in the art to best utilize the invention in various embodiments and various modifications as are suited to the particular use contemplated. It is intended that the appended claims be construed to include other alternative embodiments of the invention except insofar as limited by the prior art.

10